

INSTALLATION PROCEDURES

1. Install mounting plate/driver assembly to junction box in ceiling using mounting screws.
2. Connect the primary leads from the junction box to the primary leads of the LED Driver (Black or Brown-to-Black, White or Blue-to-White) on the LED Driver supply side. Connect the Green to the Ground wire.
3. For 0-10V Dimming, the driver can be dimmed with 0-10V dimming controls. Locate low voltage dimming control wires (purple, grey) and make appropriate connections (purple to purple, grey to grey). For Non-Dimming applications, cap off the low voltage control wires.
4. Carefully tuck excess wires and connectors in Junction box. Position the canopy in-place by aligning the two side screws on the mounting bracket to the slots on the sides of the canopy, twist and lock canopy in place, secure and tighten two (2) screws on side of canopy.
5. The pendant can now be installed by inserting the Quick Disconnect plug from pendant into canopy, twist knurled ring to tighten and secure.

For additional pendant installation details, please refer to the CRS5 LED Mini Pendant installation instructions.

IMPORTANT SAFETY INSTRUCTIONS:

- Read all the instructions before installation. Save instructions for later use.
- Turn off power at fuse or circuit breaker box before installation or before doing any maintenance work.
- Do not exceed the nominal supply voltage or amperage rating.
- Do not install any lampholder closer than 6" from any curtain or similar combustible material.
- **Warning:** Risk of burns. Lamps are extremely hot when lit. Allow lamps to cool down in temperature before handling.
- Product must be mounted in locations and at heights and in a manner consistent with its intended use, and in compliance with National Electrical Code and local codes. Use of accessory equipment is not recommended.
- Installing contrary to instructions may cause unsafe conditions.
- **Warning:** Risk of fire. Most dwellings built before 1985 have supply wire rated at 60°C. Consult a qualified electrician before installation.
- To avoid hazards to children, account for all parts and properly dispose of all packing materials.
- Call the Technical Support department at ConTech Lighting with any installation questions: 847.559.5500.

