







# Magellan Low Voltage Flexible Track System

## 12V Fixtures

### Specifications/Features

Magellan Low Voltage Flexible Track Lighting system offers unique visual interest over standard ceiling track. Crafted from high quality materials, Magellan is rated for use at 12V (300W capacity) or 24V (600W capacity) operation with an adapter integrated into every fixture to ensure a solid electrical connection and simplified

installation. Repositioning fixtures on the track is easy when lighting needs change with the Quick Disconnect feature. The silver finish adds contemporary styling. All fixtures carry ConTech's one year full replacement guarantee after date of purchase. Lamps sold separately. All fixtures are cCSAus certified for dry locations.



**Syros**

Lamp: 50W max. MR16 FG Lamp, GU5.3 base  
Length: 1-1/2"  
Finish: -S (Silver)\*



**CRS129**

**Star Spot**

Lamp: 50W max., MR16 FG Lamp, GU5.3 base  
Length: 2-3/4"; Diameter: 1-1/4"  
Finish: -S (Silver)\*



**CRS140**

**Ponti with Porcelain Shade**

Lamp: 50W max. MR16 FG Lamp, GU5.3 base or T5 Xelogen, GY6.35 base  
Length: 4-1/8"; Diameter: 2-7/16"  
Finish: -S (Silver)\*



**CRS400**

**Risa with Ring**

Lamp: 50W max., MR16 FG Lamp, GU5.3 base  
Length: 3"; Diameter: 2-3/8"  
Finish: -S (Silver)\*



**CRS4537**

**Frosted White Glass Ring**

Glass accessory for Magellan Syros (CRS129). Clips included.  
Diameter: 4"




**CRS-SP130**

**Shades for Star Spot**

Length: 1-5/8"; Diameter: 2-7/16"



**CRS-STAR-B** - Blue Glass  
**CRS-STAR-DC** - Die Cast, Silver  
**CRS-STAR-W** - Frosted White Glass




**Radar**

Lamp: 50W max. AR111, G53 base  
Length: 5"; Diameter: 4-3/8"  
Finish: -S (Silver)



**CRS382**




**Nica with Metal Shade**

Lamp: 35W max., MR16 FG Lamp, GU5.3 base  
Length: 7"; Diameter: 2-1/2"  
Finish: -S (Silver)\*



**CRS381**



**Lika Spot**

Dual Swivel lampholder. Fixture allows use of one (1) LF16 series or FA-16 filter.  
Lamp: 50W max. MR16 FG Lamp, GU5.3 base  
Length: 2-3/4"; Diameter: 3"  
Finish: -S (Silver)\*



**CRS596N**



**Varre**

Glass tube accent with curved arm and removable side louver.  
Lamp: 50W max., MR16 FG Lamp, GU5.3 base  
Length: 5-1/8"; Diameter: 2-1/2"  
Finish: -S (Silver)



**CRS1066**

\*For Antique Bronze Low Voltage Magellan Fixtures, see ConTech's Quick Release System.

\*\*On fixtures designed for use with MR16 lamps, ConTech Lighting provides a clear, tempered safety glass. This safety glass should only be used with open MR16 lamps, and not used with MR16 lamps that contain an integral glass lens. This safety glass should be removed if use of MR16 with front glass is required.

# Magellan Low Voltage Flexible Track System

## 12V Fixtures



**Rocket**

Lamp: 50W max., MR16 FG Lamp, GU5.3 base  
 Length: 2-7/16"; Diameter: 1"  
 Finish: -S (Silver)\*



**CRS281**




**Mini Pen/Frosted Cylinder**

Lamp: 20W max. T3 Xelogen, G4 base  
 Length: 2-3/4"; Diameter: 1-1/16"  
 Finish: -S (Silver)



**CRS383**




**Radia-S with Curved Arm and Porcelain Shade**

Lamp: 50W max. MR16 FG Lamp, GU5.3 base or T5 Xelogen Lamp, GY6.35 base  
 Length: 3-5/8"; Diameter: 2-15/16"  
 Finish: -S (Silver)\*



**CRS44156**




**Argos with Porcelain Shade**

Lamp: 50W max. MR16 FG Lamp, GU5.3 base or T5 Halogen Lamp, GY6.35 base  
 Length: 3-1/2"; Diameter: 2-13/16"  
 Finish: -S (Silver)



**CRS4426**




**Spot w/Satin Tulip Glass Shade**

*Includes Fingerglass*  
 Lamp: 50W max. MR16 FG Lamp, GU5.3 base or T4 Halogen Lamp, GY6.35 base  
 Length: 3-1/2"; Diameter: 3-1/8"  
 Finish: -S (Silver)



- CRS35406A** - Antique Ivory Glass
- CRS35406B** - Cobalt Blue Satin Glass
- CRS35406F** - Frost Satin Glass
- CRS35406G** - Green Satin Glass
- CRS35406R** - Red Satin Glass
- CRS35406Y** - Yellow Satin Glass



**Spot w/Satin Cone Glass Shade**

*Includes Fingerglass*  
 Lamp: 50W max. MR16 FG Lamp, GU5.3 base or T4 Halogen Lamp, GY6.35 base  
 Length: 3"; Diameter: 4-3/4"  
 Finish: -S (Silver)



- CRS35434A** - Amber Cone
- CRS35434B** - Blue Cone
- CRS35434F** - Frost Cone
- CRS35434G** - Green Cone
- CRS35434R** - Red Cone

\*For Antique Bronze Low Voltage Magellan Fixtures, see ConTech's Quick Release System.

\*\*On fixtures designed for use with MR16 lamps, ConTech Lighting provides a clear, tempered safety glass. This safety glass should only be used with open MR16 lamps, and not used with MR16 lamps that contain an integral glass lens. This safety glass should be removed if use of MR16 with front glass is required.