

CTL816TL

Eclipse Series Low Voltage Long Gimbal with Transformer

Specifications/Features

Fixture

Designed for MR16 12V LED lamps and is ideal for residential, commercial and retail lighting applications.

Long gimbal designed for low voltage (12V) MR16 Halogen lamps.

Sure-Set yoke design provides accurate aiming; holding fixture in position with one knob.

358° aiming.

For use with single circuit track only.

Lamp

50W MR16 Lamp or (1) MR16 LED Lamp, GU5.3 Base

This fixture can be used with a variety of MR16 LED Lamps. However, with the variances in these lamps, ConTech Lighting cannot be responsible, nor guarantee, that all MR16 LED lamps are universally compatible.

On fixtures designed for use with MR16 lamps, ConTech Lighting provides a clear, tempered safety glass. This safety glass should only be used with open MR16 lamps, and not used with MR16 lamps that contain an integral glass lens.

Electrical

Electronic Transformer

Input: 120V / 60Hz

Output: 12V

Rated Lamp Load: 2.5W min. to 60W max.

Dimming

Dimmable to 10% with an electronic low-voltage (ELV) dimmer.

Dimming performance may vary due to field conditions, including but not limited to, power quality, installation and wiring, and variations in dimmer production.

Please reference the dimmer manufacturer's instructions for dimmer installation and further information.

Warranty

This fixture is covered by ConTech's full one (1) year replacement guarantee after date of purchase.

Listing

cCSAus Certified. Suitable for dry locations.

Ordering Information

Example Order: -

Fixture

CTL816TL

Finish

B - Black
P - White
S - Silver

Accessories

LF16 - **A, B, CL, G, LB, R, RO, Y, 73, LS, SL, UV**

2" Tempered glass lenses

FA-16 - Honeycomb Louver

Color/Pattern Legend

-A (Amber), **-B** (Blue), **-CL** (Clear), **-LB** (Light Blue),
-R (Red), **-RO** (Rose), **-Y** (Yellow), **-73** (Spread Lens),
-LS (Linear Spread Lens), **-SL** (Soft Light),
-UV (Optivex UV Filter)

