

TLT Tapelight Series

24VDC RGBW Tapelight Accessories

Plug-In Power Supplies and Accessories



24V Plug-and-Play Power Supply
120VAC/24VDC. Includes AC wall plug and female power output plug for easy installation. Plug-in unit measures 3-1/4" L x 1-3/4" W x 1-1/4" D; system length: 6'. For use with 24V LED Tapelight only.

TLP24VP36 - 36W
TLP24VP60 - 60W
TLP24VP96 - 96W

Hardwire Power Supplies and Accessories



24V Hardwire Power Supply
120VAC/24VDC. Includes stripped and tinned wire pig-tails on the input and output sides. Must be maintained within an enclosure that meets local building codes and NEC (supplied by others). 1' Wire leads. Class II. For use with 24V LED Tapelight only.

TLP24VHW20 - 120V/20W;
5-3/4" L x 1-1/2" W x 1-1/4" D

TLP24VHW60 - 120V/60W;
6-1/3" L x 1-3/4" W x 1-1/4" D

TLP24VHW96 - 120V/96W;
8-3/4" L x 2-2/3" W x 1-1/2" D



24V Hardwire Class II Enclosed Driver
120VAC/24VDC. Dimmable Class 2 driver. Compact self-enclosed driver with two (2) knockouts. Auto Reset and short circuit protection. Triac Voltage Dimming only, not compatible with low voltage. For use with 24V LED Tapelight only.

TLP24VHW20-ENC - 120V/20W;
6-3/4" L x 2-2/3" W x 1-1/4" D

TLP24VHW60-ENC - 120V/60W;
6-3/4" L x 2-2/3" W x 1-1/4" D

TLP24VHW96-ENC - 120V/96W;
6-3/4" L x 2-2/3" W x 1-1/4" D

TLP24VHW96-ENC277V - 277V/96W;
9-7/8" L x 3" W x 3" D



Input Power Connector
Includes wire pigtail end and (1) male flex tape connector. Use with RGBW Controller, LED Power Repeater and 0-10V Dimming Module. For use with 24V LED Tapelight only.

TLCIP12HWRGBW - 12"



Output Power Connector
Includes wire pigtail end and (1) female flex tape connector. Use with RGBW Controller, LED Power Repeater and 0-10V Dimming Module. For use with 24V LED Tapelight only.

TLCOP12HWRGBW - 12"



Female Connector
6" Connector includes a wire pigtail end and a female plug connector on the other end. Used to add plug and play female connector to hardwire power supplies. For use with 12V or 24V LED Tapelight.

TLCCF



Male Connector
6" Connector includes a wire pigtail end and a male plug connector on the other end. Used for easy plug in connection to plug and play power supply and wire end can be connected to RGBW controller at the screw terminals. For use with 12V or 24V LED Tapelight.

TLCCM

Linear Connectors



Bridge Connector
Blank section used to bridge gaps where LEDs are not necessary. Field cuttable every inch, only on 6" and 12" lengths. For use with 24V LED Tapelight only.

TLCM2RGBW - 2"
TLCM6RGBW - 6"
TLCM12RGBW - 12"



Cross Connector
Can connect up to four (4) TLT RGBW segments. May be cut to create 2-way "L" connection or 3-way "T" connection. For use with 24V LED Tapelight only.

TLCXRGBW

Continued on Page 2

TLT Tapelight Series

24VDC RGBW Tapelight Accessories

Controllers



LED Power Repeater

Enables synchronized control of multiple runs from one controller. 5-5/16" L x 1-3/4" W x 1-1/8" D. For use with 24V RGBW LED Tapelight only.

TLPRPTW



DMX 512 CV Decoder

Designed to convert universal DMX 512 signal to PWM signal when used with a DMX 512 console (by others). Can control white, single color or RGBW LEDs. For use with 12V or 24V LED Tapelight. 6-3/16" L x 3-1/8" W x 1-5/8" D.

TLPINT



Switch, LED Tapelight IR Cabinet

Allows on/off switching functionality for use with cabinet doors. For use with 12V or 24V LED Tapelight. 36W MAX. 1-1/2" L x 1-3/16" W x 5/16" H

TLPICB



Switch, LED Tapelight IR Wireless Waving

Allows wireless on/off switching functionality by waving an object within the IR field. For use with 12V or 24V LED Tapelight. 36W MAX. 1-1/2" L x 1-3/16" W x 5/16" H

TLPIWV



Touch Controller

Dial Touch Controller, select color by color wheel. Speed and brightness control. Pre-selected modes. 6-7/8" L x 1-3/4" W x 1-3/16" D. For use with 12V or 24V LED Tapelight. 20AMP Max.

TLPRGBWTC



28-Key Remote Controller

28-Key RF Remote for color, speed, and brightness control. Seven (7) programmable scenes. 6-7/8" L x 1-3/4" W x 1-3/16" D. For use with 12V or 24V LED Tapelight. 20AMP Max.

TLPRGBWRF