

TLTO Tapelight Series

12VDC Wet Location High Output Accessories

Catalog No. _____

Type _____

Project _____

Power Supplies and Accessories



Wet Rated 36W Plug-and-Play Power Supply
120VAC/12VDC. Includes AC wall plug and female power output plug for easy installation. Desktop unit: 7-1/8" L x 2" W x 1-5/8" D; cord length: 6.5'.
TLPO12VP36



Wet Rated 60W Plug-and-Play Power Supply
120VAC/12VDC. Includes AC wall plug and female power output plug for easy installation. Desktop unit: 7-1/8" L x 2" W x 1-5/8" D; cord length: 6.5'.
TLPO12VP60



Wet Rated Plug-and-Play 2-Way Splitter
Includes (1) male and (2) female connectors. Approximately 22" long.
TLCOS2



Hardwire Power Supply
120VAC/12VDC. Includes stripped and tinned wire pig-tails on the input and outputsides. Must be maintained within an enclosure that meets local building codes and NEC (supplied by others). 2' Wire leads. **NOT UL LISTED FOR OUTDOOR USE.**

- TLP12VHW20** - 120V/20W;
4-3/4" L x 1-3/16" W x 1" D
- TLP12VHW60** - 120V/60W;
6-1/2" L x 1-3/4" W x 1-1/4" D
- TLP12VHW60277** - 277V/60W;
6-1/2" L x 1-3/4" W x 1-1/4" D

Controllers - Not UL Listed for Outdoor Use



LED Power Repeater
Enables synchronized control of multiple runs from one controller. 4-3/4" L x 1-1/2" W x 1-1/2" D.
TLPRPT



0-10V Dimming Module
For use with standard 0-10V dimmers. Dimming down to 15%. 4-3/4" L x 1-1/2" W x 1-1/2" D.
TLPDIM10V



DMX 512 CV Decoder
Designed to convert universal DMX 512 signal to PWM signal when used with a DMX 512 console (by others). Can control white, single color or RGB LEDs. 6-3/16" L x 3-1/8" W x 1-5/8" D.
TLPINT



Wall Plate Dimmer
Allows adjustment of the brightness of the LEDs using the knob adjustment or the IR remote control. Dimming down to 1%. 3-7/16" square x 2-1/4" deep.
TLPDIMWP



Replacement RGB Remote Control
Included with RGB Tapelight Kit; control for RGB tapelight. 3-1/4" L x 2" W x 1/4" D
TLPORGBRMT